

X1-MINI G4

SINGLE-PHASE
ON-GRID INVERTER

0.6~3.3kW



Features

Upgraded Performance

- DC Input: 200% oversizing, 16A current, 40~450V wider MPPT voltage range
- In-built global MPP scan for higher yields

Flexible Adaptability

- Adapt to Home EV Charger Solution
- Mass management and broad extension via Datahub
- Extendable parallel solution via Modbus supported


Advanced Safety

- AC/DC built-in Type II SPD (Optional) and I-V curve diagnosis supported
- Support external Rapid Shutdown device (RSD)
- Optional ARC detection (AFCI)
- Built-in export control function

Optimized Monitoring

- 10s level interval of data update (Optional)
- Multiple interfaces for presenting data

SOLUTION DESIGN



X1-MINI G4

SINGLE-PHASE

X1-MINI-0.6K-G4 X1-MINI-0.7K-G4 X1-MINI-1.1K-G4 X1-MINI-1.5K-G4 X1-MINI-2.0K-G4 X1-MINI-2.5K-G4 X1-MINI-3.0K-G4 X1-MINI-3.3K-G4

DC INPUT

Max. PV array input power [Wp]	1200	1400	2200	3000	4000	5000	6000	6600
Max. PV input voltage [V]	450	450	450	450	450	550	550	550
Startup voltage [V]	50	50	50	50	50	50	50	50
Nominal input voltage [V]	360	360	360	360	360	360	360	360
MPP tracker voltage range [V]	40~450	40~450	40~450	40~450	40~450	40~550	40~550	40~550
No. of MPP trackers / Strings per MPP tracker					1/1			
Max. PV input current [A]					16			
Isc PV Array Short Circuit current [A]					22			

AC OUTPUT

Rated AC output power [W]	600	700	1100	1500	2000	2500	3000	3300
Rated AC output current [A]	2.6	3.1	4.8	6.5	8.7	10.9	13.1	14.4
Max. AC output apparent power [VA]	600	770	1210	1650	2200	2750	3300	3300
Max. AC output current [A]	3	3.5	5.5	7.5	10	12.5	15	15
Nominal AC voltage/AC voltage range [V]**				220/230/240;90~285				220/230/240;90~290

Nominal AC frequency/AC frequency range [Hz]**				50/60;±5				
Power Factor range				0.8 leading~0.8 lagging				
THDi (Rated power) [%]				<3				

SYSTEM DATA

Max. efficiency [%]	98	98	98	98	98	98	98	98
Euro. efficiency [%]	96	96	96	97	97	97	97	97
Standby consumption [W] @Night				<1				
Ingress protection				IP66				
Protection class				Class I				
Over voltage category				II (DC),III (AC)				
Operating ambient temperature range [°C]				-25~60				
Max. operation altitude [m]				<4000				
Humidity [%]				0~100				
Typical noise emission [dB]				25				
Storage temperature [°C]				-30~70				
Dimensions (WxHxD) [mm]				290x206x120				
Weight [kg]	5.2	5.2	5.2	5.2	5.2	5.5	5.5	5.5
Cooling concept				Nature cooling				
Communication interfaces				USB/RS485/DRM, Optional: Meter/CT *				
Optional monitoring dongle				Pocket WiFi/LAN/4G				
Display				2 x LED + LCD(16 x 2) / APP				

PROTECTION

Over/under voltage protection	Yes
DC isolation protection	Yes
Monitoring ground fault protection	Yes
Grid monitoring	Yes
DC injection monitoring	Yes
Back feed current monitoring	Yes
Residual current detection	Yes
Anti-islanding protection	Yes
Over temperature protection	Yes
SPD (DC/AC)	Type II / Type II (Optional)
Arc-fault circuit interrupter (AFCI)	Optional
AC auxiliary power supply (APS)	Optional
DC Switch	Optional

STANDARD

Safety	EN/IEC62109-1/2
EMC	EN61000-6-1/2/3/4; EN61000-3-2/3/11/12
Certification	IEC61727, EN50549, G98/G99, AS 4777.2, VDE4105, CEI 0-21, VFR

* Not included in the package. Please purchase additionally.

** The AC voltage and the frequency range may vary from different country codes

* V1.1. Information may be subject to modify without notice.650.00030.00